

SECONDARY MACHINES

MACHINE	MODEL	DESCRIPTION	SPECIFICATIONS
TAPPING MACHINE	JT-6516	Gear-pitch type. Auto tapping machine with Double spindle Head adaptor (optional)	Tapping Sizes: <i>Single Spindle-</i> 3mm x .5 pitch minimum 12mm x 1.25 pitch max <i>Double Spindle-</i> 3mm x .5 pitch minimum 8mm x 1.25 pitch minimum Head Adaptor Specs: Head space: min 25mm x 151mm at 8mm x 4000 rpm
TAPPING MACHINE	JT-6516	Multispindle gear pitch type. Auto tapping machine Fixed-type Multispindle	Tapping sizes: <i>Multispindle: (4 heads)</i> 3mm x 0.5 pitch minimum 6mm x 1.25 pitch maximum
TAPPING MACHINE		Stepless Speed- variable drill/ tapping machine Single Clutch type with Double spindle head adaptor (optional)	Tapping size: <i>Single spindle -</i> 4mm up to 16mm <i>Double Spindle -</i> 4mm up to 10mm
DRILLING MACHINE	Meteor	Single Chuck Drilling machine Step pulley drive	1/2 HP motor Drill size: 3mm up to 12mm
DRILLING MACHINE	Meteor	Single Chuck Drilling machine Step pulley drive	1/2 HP motor Drill size: 3mm up to 12mm
DRILL PRESS	Arboga Maskiner	Drilling machine with moveable platen Variable speed adjustment	MAX SPEED: 2780/1310 RPM
HYDRAULIC PRESS	TP-20	Hydraulic trimming machine	Max trim force: 20 ton max stroke: 700mm Distance between tiebars: 585x280 Die space (moving): 915x610 Die space(base): 915x610 Height to base: 900mm
HYDRAULIC PRESS	DCT-20SP	Hydraulic trimming machine	Max trim force: 20 TONS Press tool max size: 600mm x 600mm
FLY WHEEL PRESS	EXACTA	Flywheel trimming press machine	Max trim force: 15 TONS Press tool max size: 300 x 400mm
FLYWHEEL PRESS	TAYLOR & CHALLENGER	Flywheel trimming press machine	Max trim force: 6 Tons